biofit.com | 800.597.0246

Amherst (AM) Series

advantage: adaptability | use: clean room, static control/ESD, various workspaces

The Amherst (AM) Series features a larger saddle-shaped seat and backrest to enhance user performance. A variety of options are available to suit your work environment, including clean room and static control/ESD performance packages. 13-year warranty.

- Cloth and vinyl upholstery styles available to match various workspace requirements.
- Saddle-shaped, contoured seat with waterfall front and internal seat board bumperguard.
- Black powder-coat finish standard on metal parts. Optional chrome or custom powder-coat colors available.
- Pneumatics are available to provide low, medium and high seat height ranges to accommodate many task requirements.
- High-profile Euro-look base with T-shape construction for added strength and easy cleanability.
- Dual-wheel non-marring polyurethane casters resist movement when the chair is unoccupied, enhancing workplace safety by inhibiting seating from rolling away.

ordering information | january 2024

Amherst Series | Standard Components

21"W x 19"D x 3"T seat, 18"W x 19"H backrest with lumbar support and plastic protective panel, soft touch pneumatic seat height adjustment; fixed rearward 3.5° seat tilt, backrest tilt and backrest height adjustment, grade 2 upholstery

Models with tubular steel base

Shown here:

with A base,

height range

low seat

Amherst Series

Model#	Seat-Hgt.	Compatibility	
AMS-L-RC-T-XF-XA-06	Low, 18"-22"	Desk	
AMS-M-RC-T-XF-XA-06	Medium, 21"-28"	Standard Bench	
AMS-H-RC-T-XF-XA-06	High, 25"–32"	High Bench	

Models with cast aluminum base

Model#	Seat-Hgt.	Compatibility	
AMA-L-RC-T-XF-XA-06	Low, 17"-22"	Desk	
AMA-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench	
AMA-H-RC-T-XF-XA-06	High, 22"-32"	High Bench	

Models with reinforced composite base			
Model#	Seat-Hgt.	Compatibility	
AMR-L-RC-T-XF-XA-06	Low, 17"-22"	Desk	
AMR-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench	
AMR-H-RC-T-XF-XA-06	High, 22"-32"	High Bench	

Models with wide aluminum base

Model#	Seat-Hgt.	Compatibility	
AMW-L-RC-T-XF-XA-06	Low, 17"-22"	Desk	
AMW-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench	
AMW-H-RC-T-XF-XA-06	High, 22"-32"	High Bench	

Ask about special and custom orders.

WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

BIOFIT



• 23" diameter tubular steel (S style) base with 21" diameter affixed footring.



 25.6" diameter, highprofile cast aluminum (A style) base.



 25.6" diameter, high-profile reinforced composite (R style) base.



• 28.7" diameter, highprofile wide aluminum (W style) base.

Component	MFG Code	Description
Seat	В	Ergonomic, concave seat with internal seat board bumperguard, 18.5"W x 16.5"D x 3"T
	E	Ergonomic with 4-way contouring and internal seat board bumperguard, 18.5"W x 17"D x 3"T
Armrest	ARS	Height/width adjustable with self-skinned urethane pads (not available with ISO 3 or 4 performance packages)
	PSAS	Height adjustable with self-skinned urethane pads
Seat Control	FFAC	Free float articulating: pneumatic seat- and backrest-height adjustment; seat and backrest tilt independently via separate levers, and can free float or lock into place; seat can tilt forward ISO 5 performance package configurations
	EXE	Executive tilt: pneumatic seat- and backrest-height adjustment; backrest tilt, seat and backrest swivel tilt in unison; tilt tension control knob and single lever seat tilt lock into any position (only available on models with maximum seat height of 26" or less)
	SLD	Seat slider bracket allows seat depth adjustment range of up to 2.5" w/locking positions every 0.5"; add to the standard Task, FFAC or EXE controls (<i>Available with Task control and R or A base in low height only; available</i> with Task Control and W base in all seat heights; not available on S style base; available with EXE control and W base only in low and medium heights, clean room models ISO 6 or higher)
	ASC	Articulating Seat Control: Pneumatic seat- and backrest-height adjustment; seat and backrest tilt independently and lock into place with a single lever (only available on ISO 3 and ISO 4 clean room models without arms)
Footring	AFP	Adjustable height, 22" diameter, oval tube construction, solid polished cast aluminum spoke (recommended for medium and high height models with A, W or R bases, adjusts easily without knobs/levers; not available with low height models or S style base units)
	ATF	Adjustable height, 20" diameter, cast aluminum (recommended for medium and high height models with A, W or R bases, not available with low height models or S style base units)
Glides	HG	2" high polyamide glides
Casters	LRO	Dual-wheel, soft tread, with weight-activated self-braking capability; resists movement when seat is occupied
	R	Single-wheel, thermoplastic rubber, non-marring, ball-bearing construction; for hard floors including concrete
	RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models
	RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (standard with ESD performance packages)
Miscellaneous	SW	Skid wrapping, net cost per pallet
	VU	Upholstered underwrap to match seat upholstery
	FM	Memory Foam

upholstery	
MFG Code	Description
COM	Customer's own material
Grade 2	Comes standard on upholstered models unless otherwise noted
Grade 3	Grade 3 upholstery
Grade 4	Grade 4 upholstery
Grade 5	Grade 5 upholstery

Category	Class	MFG Code	
ESD	-*	К	
Clean Room	ISO 8**	ISO8	
	ISO 7**	ISO7	
	ISO 6	ISO6	
	ISO 5	ISO5	
	ISO 4*	ISO4	
	ISO 3*	ISO3	
Clean Room/ESD	ISO 8/ESD*	ISO8K	
	ISO 7/ESD*	ISO7K	
	ISO 6/ESD*	ISO6K	
	ISO 5/ESD*	ISO5K	
	ISO 4/ESD*	ISO4K	
	ISO 3/ESD*	ISO3K	
Standard black metal part finish	_	06	
Chrome-plated metal parts, chairs w/A, W, R base	e —	С	
Chrome-plated metal parts, chairs w/S base	_	С	

